

SubstiTUBE® CURVALUME® IPS T8 U-Bend LED Gen 8 Lamps

Key Features and Benefits



Key features and benefits

- **High efficacy:** Up to 161 LPW lamp efficacy; 2W lower power & 15% higher LPW than current generation product
- **Power Supply –** Compatible with instant start and select programmed rapid start (parallel-wiring) electronic T8 ballasts with input voltage of 120-277V and 347V
- 0-10V Dimming
- **End-to-end illumination including the “U” bend part**
- Provides instant light and uniform light distribution plastic construction with **stable lamp to lamp color**
- Suitable for dry and damp locations; frosted plastic material
- **DLC 4.4 & ETL Sanitation listed** to NSF/ANSI Standard 2 – Food Equipment

Lamp Shape	Wattage	Lumens	CCT	DIM
T8 Ubend	13W	2100	3000K, 3500K, 4100K & 5000K	Yes

Applications: Education, Office, Retail and General Illumination

83
CRI


Dimmable


UL US


DLC LISTED


NSF

50k
Hours


5
YEAR
LIMITED WARRANTY

SubstiTUBE® CURVALUME® IPS T8 U-Bend LED Gen 8 Lamps

Product Offering

Phase Out NAED	NEW NAED	Ordering Description	Lamp Power (W)	Replaces	CCT	Lamp Lumens (lm)	Lamp LPW (lm/W)	CRI	Beam Angle(°)	Life (hours)	Case Quantity
75492	40580	LED13T8/U/FP/DIM/830/SUB/G8	13	32W T8 Ubend	3000	2100	161	83	160°	50,000	10
75493	40581	LED13T8/U/FP/DIM/835/SUB/G8	13	32W T8 Ubend	3500	2100	161	83	160°	50,000	10
75494	40582	LED13T8/U/FP/DIM/841/SUB/G8	13	32W T8 Ubend	4100	2100	161	83	160°	50,000	10
75495	40583	LED13T8/U/FP/DIM/850/SUB/G8	13	32W T8 Ubend	5000	2100	161	83	160°	50,000	10