



10025



10025-007

# 10025 Series with Hickey

Phenolic body. 25/32" dia. over lining. Snap-on lining per UL Standard 1571. With #6-32, 3/8" dia. binder head terminal screws.

**Standard pack:** bulk

- 75W-125V • UL Listed E-13400 • CSA Certified LR-1863

## Two-Leg Solid Hickey

Cat. No.	Extrusion	H Dim.
10027	Outside	1 3/4 (44.45)
10025	Outside	2 3/32 (53.18)
10027-035	Outside	3 (76.2)
10027-037	Inside	2 9/16 (65.09)
10025-010	Inside	3 1/2 (88.9)
10025-007	Inside	3 7/8 (98.43)
10025-011	Inside	4 (101.6)
10025-008	Inside	4 1/16 (103.19)

## Two-Leg Adjustable Hickey

Cat. No.	Extrusion	H Dim.
10026	Outside	3 1/2-4 5/8 (88.9-117.48)
10026-004	Inside	4 1/4-5 1/2 (107.95-139.7)

## One-Leg Solid Hickey

Cat. No.	H Dim.
10025-014	2 7/8 (73.03)
10025-012	3 (76.2)
10026-005	3 3/8 (85.73)
10025-013	3 7/8 (98.43)
10025-015	4 (101.6)
10025-016	4 1/2 (114.3)

