



STARLED[®], INC.

PILOT LIGHT INDICATOR FOR 11/16 (0.690") MOUNTING HOLE DIA.

ORDERING INFORMATION: $\frac{\text{LHSMB119}}{\text{(A)}} \frac{1}{\text{(B)}} \frac{\text{C}}{\text{(C)}} \frac{1}{\text{(D)}} - \frac{24\text{V}/25}{\text{(E)}} - \frac{\text{DP}}{\text{(F)}}$ **(A) MODEL NUMBER**

LHSMB119 (SCREW TERMINALS)

LHTMB119 (SOLDER TERMINALS)

(B) NUMBER OF LED CHIPS

1 = 1, T1-3/4 SINGLE CHIP LED

6 = 6, T1-3mm CLUSTER LED

7 = 7, T1-3mm CLUSTER LED

(C) LENS CAP COLOR

C = CLEAR TINTED

WC = WATER CLEAR

WD = WHITE DIFFUSE

(D) LED EMITTED COLOR & WAVELENGTH

1 = ULTRA RED (660nm)

2 = STD. HI EFF.. RED 630-635nm)

U2 = ULTRA HI EFF. RED (623-630nm)

U3 = ULTRA ORANGE (612-620nm)

4 = STD. YELLOW (585nm)

U4 = ULTRA YELLOW (590-595nm)

5 = STD. GREEN (565-570nm)

*6NW = ULTRA PURE GREEN (520-530nm)

*8NW = FLUORESCENT "WHITE" (NO nm VALUE)

*10NW = ULTRA BLUE (465-475nm)

*11NW = BLUISH GREEN (498-508nm)

*12NW = SOFT WHITE (No nm VALUE)

Note: *Max continuous current 10mA.**(E) STANDARD OPERATING VOLTAGES /mA.**

SINGLE CHIP LED: 5V/25, 12V/25, 24V/25, 28V/25, 48V/12 & 120V/10

6 CLUSTER LED: 5V/75, 6V/75, 12V/50, 14V/50

7 CLUSTER LED: 18V/25, 24V/25, 28V/25, 36V/25, 48V/12, 60V/15 & 120V/10

For other voltages please call factory**ALL LAMPS ARE DUAL POLARITY****Note:**

1. Materials: Body and mounting hardware-nickel plated brass< lens-high impact Plastic, terminals-tin plated brass.
2. Uses T3-1/4 Bayonet base lamps (INCANDESCENT OR LED). See specifications for MODEL MB119.
3. All lenses are fluted.
4. Minimum center to center distance: 3/4".
5. Max. Panel thickness: 13/32" (0.406")

