

LED 5FT / 6FT Type A + B Tube Series



FEATURES

- Type B Double Ended
- Type A Double Ended
- Plug & Play Dual Mode (Type A & B)
- IP40 rated
- Low thermal decay & maintenance
- No Mercury or UV
- 50,000 hours lifetime

SUITABLE APPLICATIONS

- Commercial buildings
- Hotels
- Conference rooms
- Schools
- Supermarkets
- Factories
- Hospitals
- Office Buildings
- Airports

CONSTRUCTION:

PC body with PET film and soft light.

ELECTRICAL:

Available as 110-277V input.
-20°C to 50°C, -4°F to 122°F

OPTICAL SYSTEM:

120° beam angle

INSTALLATION & MOUNTING:

Type B single or double ended.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

CONTROLS & DIMMING:

Non-dimming.



MODEL NUMBER	WATTAGE	LUMENS	EFFICACY	CRI	POWER FACTOR	THD	LENS	REPLACES
LOD-5FT26W-50K	26W	2,290LM	115LM/W	82.1	0.95	15%	Clear	46W – 50W
LOD-5FT26W-40K	26W	2,290LM	115LM/W	82.1	0.95	15%	Frosted	46W – 50W
LOD-5FT26W-50K	26W	2,290LM	115LM/W	82.1	0.95	15%	Frosted	46W – 50W
LOD-6FT26W-50K	26W	2,600LM	110LM/W	83.1	0.95	15%	Frosted	46W – 50W

Series	Length	Wattage	CCT Options	Lens
LOD	5 Foot 6 Foot	26W	4000K 5000K	F = Frosted C = Clear

MODEL NUMBER	UPC CODE
LOD-5FT26W-40K – frosted	00815586024834
LOD-5FT26W-50K – frosted	00815586029228
LOD-6FT26W-50K – frosted	00815586029204