

Ordering Number Logic

LVR	22	B		XX				RM		
FAMILY	FAMILY TYPE	GEN.	VOLTAGE	NOMINAL LUMENS	DISTRIBUTION	CRI/CCT	CONTROLS	MOUNTING	FINISH	OPTIONS
LVR = Lumination® Volumetric Refit™	22 = 2' x 2'	B = 2 nd Gen	0 = 120-277 D = 347	XX = Nominal Lumen Level	MM = Med. Curved SS = Med. Rectangular	830 = 80CRI, 3000K ¹ 835 = 80CRI, 3500K 840 = 80CRI, 4000K 850 = 80CRI, 5000K ¹ T35 = TriGain, 90CRI ⁹ , 3500k T40 = TriGain, 90CRI ⁹ , 4000k	SEE CHART BELOW	RM = Refit Mount	WHITE = White WHAM = White Antimicrobial Paint	(blank) = None CP = ChicagoPlenum EL = Emergency Light ³ BZ = Emergency Bypass ⁴ -Dual Shunt Relay to be used with building generator back up systems to override dimming DF = Dim-to-off ⁹ (must be ordered with V1 Controls code) HP = High Performance ⁵

Standard Performance⁵:

EXAMPLE CONFIGURATIONS	LUMINAIRE LUMENS	LUMINAIRE TOTAL SYSTEM WATTS	LUMINAIRE LPW
LVR22B020MM8_VQRMWHITE	2000	16.5	121
LVR22B033MM8_VQRMWHITE	3300	29.0	114
LVR22B040MM8_VQRMWHITE	4000	37.0	108
LVR22B050MM8_VQRMWHITE	5000	41.0	122

High Performance⁵:

EXAMPLE CONFIGURATIONS	LUMINAIRE LUMENS ⁶	LUMINAIRE TOTAL SYSTEM WATTS	LUMINAIRE LPW
LVR22B020MMT_VQRMWHITEHP	2400	19.0	126
LVR22B033MMT_VQRMWHITEHP	3300	25.5	129
LVR22B040MMT_VQRMWHITEHP	4000	31.0	129

Ordering Notes:

- Contact manufacturer for lead times
- Most commonly ordered for Daintree Enterprise Wireless Enabled
- Test switch is remote mounted in the ceiling, EL option not available in 347V
- Contact manufacturer prior to ordering to confirm application
- Most Standard and HP (High Performance) base SKU's are DLC, there are exceptions for 347V and EL for meeting PF and/or THD results. Please check the DLC QPL
- 5000 lumens not available in High Performance
- See product specifications section: Controls on page 4 for additional Daintree system details
- 90 CRI Trigain⁹ is only available on HP (high performance) SKU's
- Must be ordered with V1 (1% Diming) controls code

CONTROLS CODE	DESCRIPTION
V1	0-10v Dimming (1%)
VQ	0-10v Dimming
TQ	Daintree Enterprise Wireless Enabled ²
TS	Daintree Enterprise Wireless Enabled with Daintree WFA100
TZ	Daintree Enterprise Wireless with fixture integrated sensor
TT	Daintree EZ Connect Wireless with fixture integrated sensor
T1	Daintree One with fixture integrated sensor with factory programmed preset ⁴
SQ	Digital Input Driver (does not have 0-10v input) that uses a field installed accessory (in the ceiling -not the fixture) that is Daintree compatible such as Daintree One, EZ Connect or Enterprise sensors
LB	Lutron Vive - VDO or DFCSJ OEM OCC Integral Fixture Control with Sensor Daylight and Occupancy
LU	Lutron Vive - VRF or DFCSJ OEM RF Integral Fixture Control (RF only) No sensor

SENSOR KIT (FOR SQ CONTROL OPTION ONLY)	PRODUCT CODE
Daintree One/EZ Connect: LSAATT/T1FM6 (WIT100 Sensor Kit)	93098472
Daintree Enterprise: LSAATZFM6(WIZ100 Sensor Kit)	93098473
Daintree Ent. Multi Sensor: LSAATMFM6 (WMZ10 Sensor Kit)	93119594