

LED UFO High Bay
LUHB Series

Features

- Magnesium alloy heatsink
- Ultra-durable Powder Coat Paint
- Standard Color Black
- Comes standard with a high bay hanging hook. Pendant mount possible using 1/2" threaded conduit entry on top
- Fixtures included approx. 1 ft long dimming leads and approx. 6 ft long input power cable stripped at ends.
- Color Temperature: 5000K standard (cool white), other colors available (special order, lead times apply)
- Color Rendering Index (CRI): > 80
- Long LED life; L₇₀ > 50,000 hours
- Rated for Ambient Temperatures between -40°C/-40°F to 50°C/122°F
- Input Voltage: MV: 100 – 277V; 50/60 Hz
- Input Voltage: HV: 200 – 480V; 50/60 Hz
- Power Factor (PF) > 0.95
- Total Harmonic Distribution (THD) < 20%
- Dimmable: 0-10Vdc
- Distribution: 120° beam angle standard, 60/70/90° possible with reflector accessory (sold separately)
- Tempered, super transparent glass
- UL/cUL Listed
- IP65
- Warranty: 5 years

Project:	
Catalog#:	
Approved by:	

Applications

- Warehouse
- Auditorium
- Retail Space
- Manufacturing Facility



LUHB - MV Models



LUHB - HV Model



Installation Instructions



Zip File

Ordering Information

Model Series	CCT	Nominal Input Power	Input Voltage	Dimensions			Comparable to HID	DLC ID
				Diameter (in)	Height (in)	Weight (lbs)		
LUHB LED UFO High Bay	50 5000K	A: 100W, 13,000 Lm	MV 100-277V, 50/60 Hz	9.65	7.25	5.0	320W	PLP3GHIFNXB1
		B: 150W, 19,500 Lm		11.00	7.95	7.5	400W	PLQTEGWWRBV2
		C: 200W, 26,000 Lm		11.81	8.15	8.7	750W	PLUBKO24GQIE
		D: 300W, 40,500 Lm	HV* 200-480V, 50/60 Hz	11.45	10.07	17.6	1000W	Not Listed

*Call factory for lead time and minimum order quantities. LUHB50DHV is not DLC listed.

Accessories



LUHB-ALR-60
60° Aluminum Reflector
Φ 14" x 5.9" Deep




LUHB-ALR-90
90° Aluminum Reflector
Φ 14" x 6" Deep




LUHB-PCR-70
70° Polycarbonate Reflector
Φ 16" x 10.5" Deep


Photometrics




60° Reflector



70° Reflector



90° Reflector



120°, Standard/no Reflector