



Part # Reference List

| Part Number | Model Number | General Characteristics | | | | | Mechanical Package | Features |
|-------------|-----------------|-------------------------|----------------|----------------|----------------|--------------|--------------------|----------|
| | | Base Model | Operating Mode | Output Voltage | Output Current | Output Power | | |
| 20-5301 | M38-U24-1400-XP | M38-U | CC | 19-24V | 1400mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5310 | M38-U24-1660-XP | M38-U | CC | 16-24V | 1660mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5322 | M38-U30-1200-XP | M38-U | CC | 16-30V | 1200mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5302 | M38-U30-1250-XP | M38-U | CC | 20-30V | 1250mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5323 | M38-U30-1330-XP | M38-U | CC | 16-30V | 1330mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5313 | M38-U36-0850-XP | M38-U | CC | 30-36V | 850mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5303 | M38-U36-1050-XP | M38-U | CC | 24-36V | 1050mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5325 | M38-U36-1110-XP | M38-U | CC | 20-36V | 1110mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5321 | M38-U42-0750-XP | M38-U | CC | 27-42V | 750mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5315 | M38-U42-0800-XP | M38-U | CC | 32-42V | 800mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5314 | M38-U42-0850-XP | M38-U | CC | 31-42V | 850mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5304 | M38-U42-0900-XP | M38-U | CC | 28-42V | 900mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5324 | M38-U42-0950-XP | M38-U | CC | 27-42V | 950mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5329 | M38-U54-0600-XP | M38-U | CC | 36-54V | 600mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5305 | M38-U54-0700-XP | M38-U | CC | 37-54V | 700mA | 40-Watts | Med Rectangle | AC Dimm® |
| 20-5312 | M38-U54-0740-XP | M38-U | CC | 35-54V | 740mA | 40-Watts | Med Rectangle | AC Dimm® |

Model Number Structure:

M 38 - U 42 - 0900 - XP

1. 2. - 3. 4. - 5. - 6.

- 1. Product Family:** M = Multi-Purpose Family
- 2. Output Power:** 38 = 40-Watts Max
- 3. Input Voltage:** U = 100-277VAC
- 4. Output Voltage:** 24, 30, 36, 42 & 54VDC
- 5. Output Current:** 0900 = 900mA
- 6. Mechanical Package:** XP = Plastic, V0 Flamability Rating

Important Notes:

- A This list intended as a Part Number Reference List as such is for reference use only. New part numbers are added on a continuous basis.
- B In the event the model # or characteristics you are looking are not found on this part# list please contact your Magtech Sales Application
- C **Output Power:** Is the maximum driver Output Power Rating as defined per our UL certification.
- D **Mechanical Package:** Please refer to the Case Drawings located in the Product Documentation section of the Technical Library.
- E **Standard Features:** AC Dimm® U versions come standard with AC Trailing Edge Dimming (for ELV Dimming Controls)

Magtech, "The Power to Drive Green Innovations"