STARLED®, INC.

T-3¼ MINIATURE BAYONET & SCREW BASE 6 & 7 CLUSTER LEDs

ORDERING INFORMATION:

MB119	6	WC	2	-	24V/25	-	DP
(A)	(B)	(C)	(D)		(E)		(F)

(A) MODEL
MB119, MS119
MBF119, MSF119 (FLAT-TOP)

(B) NUMBER OF LEDs
6 = 6, T1 3mm CLUSTER LED
7 = 7, T1 3mm CLUSTER LED

(C) LED LENS COLOR
WC = WATER CLEAR

(D) LED EMITTING COLOR & WAVELENGTH
1 = ULTRA RED (660nm) **OBSOLETE**
2 = STD. RED (630-635nm)
U2 = ULTRA HI EFF, RED (623-630nm)
3 = STD. ORANGE (605-610nm)
U3 = ULTRA ORANGE (612-620nm)
4 = STD. YELLOW (585nm)
*S4 = ULTRA YELLOW (590-595nm)
5 = STD. GREEN (565-570nm)
* 6NW = ULTRA PURE GREEN (520-530nm)
* 8NW = FLUORESCENT "WHITE" (NO nm VALUE)
*10NW = ULTRA BLUE (465-475nm)
*12NW = SOFT WHITE (NO nm VALUE)
* **Max. Continuous current 10mA.**

6 CLUSTER



MODEL: MB119



6 CLUSTER



MODEL: MBF119



(E) STANDARD DC & AC OPERATING VOLTAGES/mA
6 CLUSTER LED: 6V/75, 12V/50 & 14V/50
7 CLUSTER: 18V/25, 24V/25, 28V/25, 36V/25, 48V/12, 60V/15 & 120V/10
Note: Please call factory for other voltages.

(F) CENTER CONTACT POLARITY
DP = DUAL POLARITY

7 CLUSTER



MODEL: MS119



DIRECT INCANDESCENT LAMP REPLACEMENTS
MB- 6MB, 14MB, 24MB, 28MB, 48MB, 60MB, 120MB, 1819, 1828, 1835, ETC...
MS- 40, 46, 1487, 1821, 1832, ETC...

HOUSING MAT'L. UL94-VO APPROVED

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE