STARLED®, INC.

T-1¾ S.C. MIDGET FLANGE & MIDGET GROOVE BASE MULTI-CHIP LEDs

ORDERING INFORMATION:

MF63	2	C	1	-	24V/15	-	PC
(A)	(B)	(C)	(D)		(E)		(F)

(A) MODEL
MF63
MG63

(B) NUMBER OF LEDs
*2 = 1, 2 CHIPS T-1¾ LED
**3 = 1, 3 CHIPS T-1¾ LED
6 = 1, 6 CHIPS T-1¾ LED

(C) LED LENS COLOR
C = CLEAR

(D) LED EMITTING COLOR & WAVELENGTH
1 = ULTRA RED (660nm)
2 = STD. RED (630-635nm)
U2 = ULTRA HI EFF. RED (623-630nm)
3 = STD. ORANGE (605-610nm)
U3 = ULTRA ORANGE (612-620nm)
4 = STD. YELLOW (585nm)
U4 = ULTRA YELLOW (590-595nm)
5 = STD. GREEN (565-570nm)
*6NW = ULTRA PURE GREEN (520-530nm)

MODEL: MF63



(E) STANDARD DC & AC OPERATING VOLTAGES
* **2 CHIPS LED:** 5V/20, 6V/20, 12V/20, 14V/20, 24V/15 & 28V/15
** **3 CHIPS LED:** 24V/10, 28V/10, 36V/10, 48V/10, 60V/10 & 120V/6
6 CHIPS LED:6V/45, 12V/30, 14V/30, 24V/15, 28V/15, 36V/12, 48V/12, 60V/15 & 120V/6
* **MAX. CONTINUOUS CURRENT 20mA.**
** **MAX. CONTINUOUS CURRENT 10mA.**
NOTE: PLEASE CONTACT FACTORY FOR OTHER VOLTAGES

MODEL: MG63

(F) CENTER CONTACT POLARITY
PC = POSITIVE CENTER, NC = NEGATIVE CENTER
DP = DUAL POLARITY
DP STD. COLORS VOLTAGES AVAILABLE FROM 6V TO 120V.
DP ULTRA COLORS AVAILABLE FROM 28V TO 120V.



DIRECT INCANDESCENT LAMP REPLACEMENTS
MF63: 269, 327, 328, 330, 344, 345, 350, 376, 459, 7341, 8918, ETC...
MG63: CALL FACTORY

HOUSING MAT'L. UL94-VO APPROVED

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

2059 E. DEL AMO BLVD. * RANCHO DOMINGUEZ, CA 90220 * TEL: (310) 603-0403 * FAX: (310) 603-1335