

Project Name:	Type:
Part Number:	Date:



2" MINIFIT MODULE

SPECIFICATION FEATURES

- **Mechanical** - 2" MINIFIT module with external driver snaps into field interchangeable trims and install from below the ceiling. Trim mounted spring action clips accommodate ceiling thicknesses between 1/2" and 2".
- **Electrical** -120V, 50/60 Hz driver. Dimmable to 10% with Forward phase (TRIAC) / Reverse phase (ELV) dimmers. Plenum rated quick connect cable allows for easy wiring.
- **Optical** - 2700K, 3000K, 4000K and 5000K color temperatures available. 38° narrow beam distribution. COB technology ensures minimum 90CRI with 3-step SDCM. Open Round Flat and Round Deep Trims tilt up to 45°. Field interchangeable reflectors available with Round Deep Trims.
- **Thermal** - Extruded aluminum heat sink. Rated L70 lifetime of 50,000 hours. Ambient temperature rating: -4°F to 104°F (-20°C to 40°C).
- **Compliance and Warranty** – ETL Listed for Damp location. ETL listed for Wet location when used with Glass trims (MM2T/RFT/GL/xx). IC rated. Energy Star® listed. JA8 Certified to meet CA Title 24 requirements. 5 year parts warranty for complete fixture.



BENEFITS

- Shallow form factor for easy installation
- IC Rated and wet location listed with glass trims
- 120V dimmable down to 10%
- Multiple choice of finish and options

APPLICATIONS

- New construction and retrofit application
- Shallow plenum applications: including soffits, bulkheads, and casework
- Residential & Hospitality
- Retail & Office

ORDERING INFORMATION

Module						Trims		
Series	Size	CRI	CCT	Beam Angle	Dimming	Trim	Style	Finish
<input checked="" type="checkbox"/> MM Mini Module	<input checked="" type="checkbox"/> 2 2" 780lm	<input checked="" type="checkbox"/> 90 CRI 90	<input type="checkbox"/> 27 2700K	<input checked="" type="checkbox"/> FL Flood 38°	<input checked="" type="checkbox"/> DIM120 120V - Line voltage dimming	<input checked="" type="checkbox"/> MM2T MM2 Trim	<input type="checkbox"/> RFT/OP Round Flat - Open	<input type="checkbox"/> WH White <input type="checkbox"/> BM* Brushed Metal
			<input type="checkbox"/> 30 3000K				<input type="checkbox"/> RFT/GL Round Flat - Glass Cover	
			<input type="checkbox"/> 40 4000K				<input type="checkbox"/> RDT/OP Round Deep - Open	
			<input type="checkbox"/> 50 5000K				<input type="checkbox"/> RDT/PN Round Deep - Pinhole	
							<input type="checkbox"/> RDT/WW Round Deep - Wall Wash	

*Brushed Metal finish is only available for Round Flat trims.

SELECTION*

Ex: MM2-9030-FL-DIM120
MM2T-RFT/OP-BM

MM2	2	90		FL	DIM120
MM2T					

*A complete fixture consists of two items, one module and one trim, ordered separately.