



T-3 1/4 SCREW BASE SINGLE CHIP LEDs

ORDERING INFORMATION: MS111 WC U2 - 24V/10 - DP
(A) (B) (C) (D) (E)

(A) MODEL

MS11= SINGLE DOME LED
MSF111= FLAT-TOP SINGLE LED
RMS1191 = SINGLE DOME LED

(B) LED LENS COLOR

WC= WATER CLEAR

(C) LED EMITTING COLOR & WAVELENGTH

U2= ULTRA HI EFF. RED (623-630nm)
U3= ULTRA ORANGE (612-620nm)
*S4= ULTRA YELLOW (590-595nm)
*6NW= ULTRA PURE GREEN (520-530nm)
*8NW= FLUORESCENT "WHITE" (NO nm VALUE)
*10NW= ULTRA BLUE (465-475nm)
*11NW= BLUISH GREEN (498-508nm)
*12NW= SOFT WHITE (NO nm VALUE)
*MAX. CONTINUOUS CURRENT 10mA.

(D) STANDARD DC & AC OPERATING VOLTAGES/mA

5V/10, 12V/10, 24V/10, 28V/10, 36V/10, 48V/10, 60V/10 & 120V/6

MAX. CONTINUOUS CURRENT @ 120V/6mA

*VOLTAGES FROM 5-60V/10mA

NOTE: PLEASE CALL FACTORY FOR OTHER VOLTAGES

(E) CENTER CONTACT POLARITY

DP= DUAL POLARITY

DIRECT INCANDESCENT LAMP REPLACEMENTS

53, 55, 57

HOUSING MAT'L. UL94VO APPROVED

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

