

**Presented By:** Candela Corporation  
Contact Phone: (800) 922-9226  
Contact E-mail: sales@candelacorp.com

Customer Name:  
Project Name:  
Fixture Type:



GE  
Lighting

### 43703 - Q300T3/CL-6PK

GE Quartzline® T2.5 - Stage & Studio



#### GENERAL CHARACTERISTICS

Lamp Type	Halogen - Double-Ended
Bulb	T2.5
Base	Recessed Single Contact (R7s)
Filament	C-8
Bulb Finish	Clear
Wattage	300
Voltage	120
Rated Life	2000 hrs
Primary Application	Stage & Studio

#### PHOTOMETRIC CHARACTERISTICS

Initial Lumens	5950
Color Temperature	2950 K
Nominal Initial Lumens per Watt	19

#### ELECTRICAL CHARACTERISTICS



Burn Position	Horizontal
---------------	------------

#### DIMENSIONS

Maximum Overall Length (MOL)	4.688 cm
Bulb Diameter (DIA)	0.312 cm
Bulb Diameter (DIA) (MAX)	0.312 cm
Light Center Length (LCL)	2.25 cm

#### PRODUCT INFORMATION

Product Code	43703
Description	Q300T3/CL-6PK
ANSI Code	EHM
Standard Package	Master
Standard Package GTIN	10043168437032
Standard Package Quantity	144
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	144
UPC	043168437035



#### CAUTIONS & WARNINGS

##### Caution

- Lamp emits UV radiation which may cause eye/skin irritation. RG-1
  - Minimize exposure.
- Lamp may shatter and cause injury if broken
  - Dispose of lamp in a closed container.
  - Do not use lamp if outer glass is scratched or broken.

##### Warning

- Risk of Electric Shock
  - Turn power off before inspection, installation or removal.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
  - Do not exceed 110% of rated voltage.
  - Do not touch glass with bare hands.
  - Do not use lamp if outer glass is scratched or broken.
  - Operate lamp only in specified position -- see instructions.
  - Use eye protection when handling lamp.
  - Use in enclosed fixture rated for this product.
- Risk of Burn
  - Allow lamp to cool before handling.
  - Turn power off before installing lamp.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in enclosed fixture rated for this product.