



upgrade existing fluorescent lamps & ballasts to LEDs & drivers



- Lutron compatibility between installed control system & existing fixture
 - EcoSystem digital control – dims down to 1%
 - 3-wire phase control – dims down to 1%
- 0-10V – dims down to 5%
- Line voltage dimming (5% Dimming Typical. 120V/277V Switched; 120V only for dimming)
- Contact us for other driver types
- Retrofit for over 50% less than installing a new fixture
- Simplest & safest way to achieve energy savings
- Keep existing fixtures, controls, sensors & programming capability
- No mess/fixture recycling; no need to break ceiling plane
- Substantial maintenance & energy savings
- Optimize local utility rebates



available kits include

- T8 2', 3' & 4' G13 Base
- T5 2', 3' & 4' G5 Base
- T5HO 2', 3' & 4' G5 Base
- Troffer Transformer 2x2, 1x4, 2x4 (Refer to C-Flex Troffer Transformer Spec Sheet for ordering detail)
- LBE/BAR KIT
- PLL/BIAX 2G11 Base
- CFL/PL G24Q Base

For more information please visit c-flexretrofits.com

ETL CLASSIFIED



When searching the DLC QPL, use quotation marks around our brand name or Part # ("C-Flex" or "RP-T5-4FT-2L-840-E1-M-G2") or visit our website for a file that contains the DLC Product ID.



CORPORATE HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949
 847.380.3540 • c-flexretrofits.com

C-Flex LUTRON, 0-10V, LVD RETROFIT KITS

MOST COMMON FIXTURE TYPES



Direct/Indirect Pendants



Recessed/Slot




High Bay



1x4, 2x2 & 2x4 Parabolic/
Diffused/Architectural Troffers



Downlights



Cove & Ambient Lighting

MOST COMMON END USERS/VERTICAL MARKETS



University/Schools



Commercial Office



Government



Hospitality



Healthcare



Warehouse/Big Box



Gymnasium +
Recreation Areas

EXAMPLE KIT OPTIONS



T8 2', 3' & 4'



T5 2', 3' & 4'/T5HO 2', 3' & 4'



LBE/BAR KIT



PLL/BIAX 2G11 Base



CFL/PL G24Q Base



Troffer Transformer - Volumetric and Flat Panel
(Refer to C-Flex Troffer Transformer Spec
Sheet for ordering detail)

CHOOSE YOUR LIGHT ENGINE

PAIR IT WITH A GENUINE LUTRON DRIVER AND ACCESSORIES



Genuine Lutron Driver



Service
Disconnect



Latch
Connectors

C-Flex

CORPORATE HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949
847.380.3540 • c-flexretrofits.com

C-Flex LUTRON, 0-10V, LVD RETROFIT KITS

PART NUMBER BUILDER

MFR	PRODUCT	SIZE/LM	# OF LAMPS	COLOR (XX)	DIMMING (DD)	CASE (C)	GEN	OPTIONS (SEE BELOW)
RP	T8LO T8HO T8 T5 T5HO BARLO BAR BARHO 2FT 3FT 4FT 2.5K 5.0K 7.5K 126V 126H 132V 132H 142V 142H 226V 226H 232H 242H	1L 2L 3L 4L	830 = 3000K 835 = 3500K 840 = 4000K 850 = 5000K	E1 = LUTRON ECO SYSTEM 1 DIMS DOWN TO 1% 3W = LUTRON 3 WIRE DIMS DOWN TO 1% 10V = 0-10V DIMMING - (TLED, PLL & BAR KITS REQUIRE WATTAGE OPTION: SEE BELOW FOR AVAILABLE OPTIONS) DIMS DOWN TO 5% LVD = LINE VOLTAGE DIMMING (5% DIMMING TYPICAL. 120V/277V SWITCHED; 120V ONLY FOR DIMMING) DA = DALI DIMS DOWN TO 1%	K = SQUARE W/STUDS KN = SQUARE W/O STUDS M = LINEAR (SEE DIMENSIONS ON LAST PAGE)	G2	EMG W B TAA	

OPTIONS

EMG = Emergency Battery Backup
Approximately 500 lumens for 90 minutes.
Contact us for more options

W = Specific Wattage
Only available for TLED, PLL and bar kits with
0-10V driver option. Not used with G24Q kits
(See pages 5-11 for wattage and lumen options)

B = Bulk Pack options
B24 = 1-lamp kit
B12 = 2-lamp kit
B8 = 3-lamp kit
B6 = 4-lamp kit

TAA = TRADE AGREEMENT ACT
(not available for PLL OR G24Q lamp types)

ORDERING EXAMPLES RP-T5-4FT-2L-830-E1-M-G2
RP-T8-4FT-1L-830-10V-M-G2-10W

To specify a C-Flex Troffer Transformer Kit, refer to C-Flex Troffer Transformer Spec Sheet

ORDERING GUIDE (USE PART NUMBER BUILDER ABOVE TO COMPLETE PART NUMBER)

PART #	E1-M	3W-M	10V	LVD	LAMPS PER DRIVER	SYSTEM LUMENS*	SYSTEM WATTAGE*
BARLO	RP-BARLO-4FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1835	15
	RP-BARLO-4FT-2L-8XX-DD-C-G2	Y	Y	Y	2	3670	30
BAR	RP-BAR-2FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1476	12
	RP-BAR-2FT-2L-8XX-DD-C-G2	Y	Y	Y	2	2153	17
	RP-BAR-2FT-3L-8XX-DD-C-G2	Y	Y	Y	3	3383	27
	RP-BAR-2FT-4L-8XX-DD-C-G2	Y	Y	Y	4	4613	36
	RP-BAR-3FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1476	12
	RP-BAR-3FT-2L-8XX-DD-C-G2	Y	Y	Y	2	2153	17
	RP-BAR-3FT-3L-8XX-DD-C-G2	Y	Y	Y	3	3383	27
	RP-BAR-3FT-4L-8XX-DD-C-G2	Y	Y	Y	4	4613	36
	RP-BAR-4FT-1L-8XX-DD-C-G2	Y	Y	Y	1	2153	17
	RP-BAR-4FT-2L-8XX-DD-C-G2	Y	Y	Y	2	4305	34
	RP-BAR-4FT-3L-8XX-DD-C-G2	Y	Y	Y	3	6458	51
	RP-BAR-4FT-4L-8XX-DD-C-G2	Y	Y	Y	4	8610	68
BARHO	RP-BARHO-2FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1722	14
	RP-BARHO-2FT-2L-8XX-DD-C-G2	Y	Y	Y	2	3383	27
	RP-BARHO-2FT-3L-8XX-DD-C-G2	Y	Y	Y	3	5166	41
	RP-BARHO-3FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1722	14
	RP-BARHO-3FT-2L-8XX-DD-C-G2	Y	Y	Y	2	3383	27
	RP-BARHO-3FT-3L-8XX-DD-C-G2	Y	Y	Y	3	5166	41
	RP-BARHO-3FT-4L-8XX-DD-C-G2	Y	Y ²	Y	4	6765	53
	RP-BARHO-4FT-1L-8XX-DD-C-G2	Y	Y	Y	1	3383	27
	RP-BARHO-4FT-2L-8XX-DD-C-G2	Y	Y ²	Y	2	6765	53
PLL	RP-PLL-2.5K-1L-8XX-DD-C-G2	Y	Y	Y	1	2500	25
	RP-PLL-5.0K-2L-8XX-DD-C-G2	Y	Y	Y	2	5000	50
	RP-PLL-7.5K-3L-8XX-DD-C-G2	Y	Y	Y ¹	3	7500	70

Y¹: 10% reduction in lumens and wattage Y²: 20% reduction in lumens and wattage

* System lumens and wattage specifications are based on DLC data where available, Ecosystem drivers and 4000K lamps. Actual lumens and wattage may vary depending on driver and lamp color.

For BAA projects, please contact our projects quotations team.



CORPORATE HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949

847.380.3540 • c-flexretrofits.com

01.06.25 Information is subject to change without notice.

The Lutron logo, EcoSystem, and Lutron are trademarks or registered trademarks of Lutron Electronics Co., Inc., in the U.S. and/or other countries.

C-Flex LUTRON, 0 - 10V, LVD RETROFIT KITS

ORDERING GUIDE (CONTINUED)

	PART #	E1-M	3W-M	LVD	LAMPS PER DRIVER	SYSTEM LUMENS*	SYSTEM WATTAGE*
T5	RP-T5-2FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1544	13
	RP-T5-2FT-2L-8XX-DD-C-G2	Y	Y	Y	2	2252	25
	RP-T5-3FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1544	13
	RP-T5-3FT-2L-8XX-DD-C-G2	Y	Y	Y	2	2252	25
	RP-T5-4FT-1L-8XX-DD-C-G2	Y	Y	Y	1	2252	19
	RP-T5-4FT-2L-8XX-DD-C-G2	Y	Y	Y	2	4505	37
T5HO	RP-T5HO-2FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1802	15
	RP-T5HO-2FT-2L-8XX-DD-C-G2	Y	Y	Y	2	3539	29
	RP-T5HO-2FT-3L-8XX-DD-C-G2	Y	Y	Y	3	5405	44
	RP-T5HO-3FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1802	15
	RP-T5HO-3FT-2L-8XX-DD-C-G2	Y	Y	Y	2	3539	29
	RP-T5HO-3FT-3L-8XX-DD-C-G2	Y	Y	Y	3	5405	44
	RP-T5HO-4FT-1L-8XX-DD-C-G2	Y	Y	Y	1	3539	29
	RP-T5HO-4FT-2L-8XX-DD-C-G2	Y	Y ²	Y	2	7079	58
	RP-T5HO-4FT-3L-8XX-DD-C-G2	Y			3	10618	87
T8LO	RP-T8LO-4FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1680	17
	RP-T8LO-4FT-2L-8XX-DD-C-G2	Y	Y	Y	2	3360	29
	RP-T8LO-4FT-3L-8XX-DD-C-G2	Y	Y	Y	3	5040	41
	RP-T8LO-4FT-4L-8XX-DD-C-G2	Y		Y	4	6720	53
T8	RP-T8-2FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1496	12
	RP-T8-2FT-2L-8XX-DD-C-G2	Y	Y	Y	2	2182	18
	RP-T8-2FT-3L-8XX-DD-C-G2	Y	Y	Y	3	3429	28
	RP-T8-2FT-4L-8XX-DD-C-G2	Y	Y	Y	4	4676	38
	RP-T8-3FT-1L-8XX-DD-C-G2	Y	Y	Y	1	1496	12
	RP-T8-3FT-2L-8XX-DD-C-G2	Y	Y	Y	2	2182	18
	RP-T8-3FT-3L-8XX-DD-C-G2	Y	Y	Y	3	3429	28
	RP-T8-3FT-4L-8XX-DD-C-G2	Y	Y	Y	4	4676	38
	RP-T8-4FT-1L-8XX-DD-C-G2	Y	Y	Y	1	2182	18
	RP-T8-4FT-2L-8XX-DD-C-G2	Y	Y	Y	2	4365	35
	RP-T8-4FT-3L-8XX-DD-C-G2	Y	Y ¹	Y	3	6547	53
	RP-T8-4FT-4L-8XX-DD-C-G2	Y			4	8729	71
T8HO	RP-T8HO-4FT-1L-8XX-DD-C-G2	Y	Y	Y	1	3220	28
	RP-T8HO-4FT-2L-8XX-DD-C-G2	Y	Y	Y	2	6440	51
	RP-T8HO-4FT-3L-8XX-DD-C-G2	Y			3	9660	74

Y¹: 10% reduction in lumens and wattage Y²: 20% reduction in lumens and wattage

* System lumens and wattage specifications are based on DLC data where available, Ecosystem drivers and 4000K lamps. Actual lumens and wattage may vary depending on driver and lamp color.

Refer to Part Number Builder on page 3 for complete kit part number detail. PL lamps are not rated for use in enclosed fixtures.

	REPLACES CFL		VERTICAL					HORIZONTAL				
	LAMP QTY	LAMP WATTAGE	SYSTEM WATTAGE	LUMENS	LED LAMP IMAGE	LAMP QTY	KIT PART #	SYSTEM WATTAGE	LUMENS	LED LAMP IMAGE	LAMP QTY	KIT PART #
CFL/PL G24Q	1	26	12	900	A	1	RP-G24Q-126V-1L-8XX-DD-C-G2	13	1000	B	1	RP-G24Q-126H-1L-8XX-DD-C-G2
	2	26	24	1800	A	2	RP-G24Q-226V-2L-8XX-DD-C-G2	26	2000	B	2	RP-G24Q-226H-2L-8XX-DD-C-G2
	1	32	14	1200	C*	1	RP-G24Q-132V-1L-8XX-DD-C-G2	14	1200	D**	1	RP-G24Q-132H-1L-8XX-DD-C-G2
	2	32	N/A	N/A	N/A	N/A	N/A	24	2400	F**	1	RP-G24Q-232H-1L-8XX-DD-C-G2
	1	42	28	2700	E*	1	RP-G24Q-142V-1L-8XX-DD-C-G2	21	2000	F**	1	RP-G24Q-142H-1L-8XX-DD-C-G2
	2	42	N/A	N/A	N/A	N/A	N/A	28	2700	F**	1	RP-G24Q-242H-1L-8XX-DD-C-G2

*Depending on luminaire design, vertical downlights may benefit from having the lamp mounted lower in the luminaire. In those cases, a vertical socket extender is available; order item number: LED-7319

**Shipped with horizontal-to-vertical adapter LED-7317-ARM. May not fit in all 6" cans; test-for-fit.

Note: LVD M and K case driver options are not available for 1-lamp 26W and 32W fluorescent CFL replacement kits.



A
Replaces
up to 26W
G24q Base
(Vertical)



B
Replaces
up to 26W
G24q Base
(Horizontal)



C
Replaces
up to 32W
G24q Base
(Vertical)



D
Replaces
up to 32W
G24q Base
(Horizontal)



E
Replaces
up to 42W
G24q Base
(Vertical)



F
Replaces
up to 42W
G24q Base
(Horizontal)



LED-7319
Vertical Extender
For Vertical
32W & 42W
applications

C-Flex

CORPORATE HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949
847.380.3540 • c-flexretrofits.com

01.06.25 Information is subject to change without notice.

The Lutron logo, EcoSystem, and Lutron are trademarks or registered trademarks of Lutron Electronics Co., Inc., in the U.S. and/or other countries.

C-Flex LUTRON, 0 -10V, LVD RETROFIT

0-10V Kit Ordering Information

- 0-10V Dimmable driver with 12V Aux sensor-ready output
- Dim-to-off
- Four drivers available with maximum wattages of 12W, 25W, 45W and 80W
- Each driver has four adjustable wattage settings via DIP switches
- See ordering guide below for available lumen packages

CAUTION! MAX WATTAGE SETTING PER LAMP

	T5	T8
2FT:	15	10
3FT:	15	12
4FT:	25	25



ORDERING GUIDE FOR T5/T5HO/T8 0-10V KITS ONLY

	PART #	LAMPS PER DRIVER	LAMP LENGTH (FT)	SYSTEM LUMENS*	PERFORMANCE CATEGORY	PRODUCT ID
6W	T5	RP-T5-2FT-1L-8XX-10V-M-G2-6W	1	2	792	
		RP-T5-3FT-1L-8XX-10V-M-G2-6W	1	3	792	
		RP-T5-4FT-1L-8XX-10V-M-G2-6W	1	4	846	
	T8	RP-T8-2FT-1L-8XX-10V-M-G2-6W	1	2	864	
		RP-T8-3FT-1L-8XX-10V-M-G2-6W	1	3	828	
		RP-T8-4FT-1L-8XX-10V-M-G2-6W	1	4	858	
8W	T5	RP-T5-2FT-1L-8XX-10V-M-G2-8W	1	2	1056	
		RP-T5-3FT-1L-8XX-10V-M-G2-8W	1	3	1056	
		RP-T5-4FT-1L-8XX-10V-M-G2-8W	1	4	1128	
	T8	RP-T8-2FT-1L-8XX-10V-M-G2-8W	1	2	1152	
		RP-T8-3FT-1L-8XX-10V-M-G2-8W	1	3	1104	
		RP-T8-4FT-1L-8XX-10V-M-G2-8W	1	4	1144	
10W	T5	RP-T5-2FT-1L-8XX-10V-M-G2-10W	1	2	1320	
		RP-T5-2FT-2L-8XX-10V-M-G2-10W	2	2	1320	
		RP-T5-3FT-1L-8XX-10V-M-G2-10W	1	3	1320	
		RP-T5-4FT-1L-8XX-10V-M-G2-10W	1	4	1410	
	T8	RP-T8-2FT-1L-8XX-10V-M-G2-10W	1	2	1440	
		RP-T8-2FT-2L-8XX-10V-M-G2-10W	2	2	1440	
		RP-T8-3FT-1L-8XX-10V-M-G2-10W	1	3	1380	
		RP-T8-4FT-1L-8XX-10V-M-G2-10W	1	4	1430	
12W	T5	RP-T5-2FT-1L-8XX-10V-M-G2-12W	1	2	1584	
		RP-T5-2FT-2L-8XX-10V-M-G2-12W	2	2	1584	
		RP-T5-2FT-3L-8XX-10V-M-G2-12W	3	2	1584	
		RP-T5-3FT-1L-8XX-10V-M-G2-12W	1	3	1584	
		RP-T5-3FT-2L-8XX-10V-M-G2-12W	2	3	1584	
		RP-T5-4FT-1L-8XX-10V-M-G2-12W	1	4	1692	
		RP-T5-4FT-2L-8XX-10V-M-G2-12W	2	4	1692	
	T8	RP-T8-2FT-2L-8XX-10V-M-G2-12W	2	2	1728	
		RP-T8-2FT-3L-8XX-10V-M-G2-12W	3	2	1728	
		RP-T8-3FT-1L-8XX-10V-M-G2-12W	1	3	1656	
		RP-T8-3FT-2L-8XX-10V-M-G2-12W	2	3	1656	
		RP-T8-4FT-1L-8XX-10V-M-G2-12W	1	4	1716	
		RP-T8-4FT-2L-8XX-10V-M-G2-12W	2	4	1716	
15W	T5	RP-T5-2FT-2L-8XX-10V-M-G2-15W	2	2	1980	
		RP-T5-2FT-3L-8XX-10V-M-G2-15W	3	2	1980	
		RP-T5-3FT-1L-8XX-10V-M-G2-15W	1	3	1980	
		RP-T5-3FT-2L-8XX-10V-M-G2-15W	2	3	1980	
		RP-T5-3FT-3L-8XX-10V-M-G2-15W	3	3	1980	
		RP-T5-4FT-1L-8XX-10V-M-G2-15W	1	4	2115	
		RP-T5-4FT-2L-8XX-10V-M-G2-15W	2	4	2115	
	T8	RP-T8-2FT-2L-8XX-10V-M-G2-15W	2	2	2160	
		RP-T8-2FT-3L-8XX-10V-M-G2-15W	3	2	2160	
		RP-T8-3FT-2L-8XX-10V-M-G2-15W	2	3	2070	
		RP-T8-3FT-3L-8XX-10V-M-G2-15W	3	3	2070	
		RP-T8-4FT-1L-8XX-10V-M-G2-15W	1	4	2145	
		RP-T8-4FT-2L-8XX-10V-M-G2-15W	2	4	2145	

*SYSTEM LUMENS is calculated based on 4000K lamp design parameters. Actual lumen output will vary depending on lamp color and driver efficiency based on wattage setting.



CORPORATE HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949
 847.380.3540 • c-flexretrofits.com

01.06.25 Information is subject to change without notice.

The Lutron logo, EcoSystem, and Lutron are trademarks or registered trademarks of Lutron Electronics Co., Inc., in the U.S. and/or other countries.

ORDERING GUIDE FOR T5/T5HO/T8 0-10V KITS ONLY

		PART #	LAMPS PER DRIVER	LAMP LENGTH (FT)	SYSTEM LUMENS*	PERFORMANCE CATEGORY	PRODUCT ID
18W	T5	RP-T5-2FT-2L-8XX-10V-M-G2-18W	2	2	2376		
		RP-T5-2FT-3L-8XX-10V-M-G2-18W	3	2	2376		
		RP-T5-2FT-4L-8XX-10V-M-G2-18W	4	2	2376		
		RP-T5-3FT-2L-8XX-10V-M-G2-18W	2	3	2376		
		RP-T5-3FT-3L-8XX-10V-M-G2-18W	3	3	2376		
		RP-T5-3FT-4L-8XX-10V-M-G2-18W	4	3	2376		
		RP-T5-4FT-1L-8XX-10V-M-G2-18W	1	4	2538		
		RP-T5-4FT-2L-8XX-10V-M-G2-18W	2	4	2538		
	T8	RP-T5-4FT-3L-8XX-10V-M-G2-18W	3	4	2538		
		RP-T8-2FT-2L-8XX-10V-M-G2-18W	2	2	2592		
		RP-T8-2FT-3L-8XX-10V-M-G2-18W	3	2	2592		
		RP-T8-2FT-4L-8XX-10V-M-G2-18W	4	2	2592		
		RP-T8-3FT-2L-8XX-10V-M-G2-18W	2	3	2484		
		RP-T8-3FT-3L-8XX-10V-M-G2-18W	3	3	2484		
		RP-T8-3FT-4L-8XX-10V-M-G2-18W	4	3	2484		
		RP-T8-4FT-1L-8XX-10V-M-G2-18W	1	4	2574		
		RP-T8-4FT-2L-8XX-10V-M-G2-18W	2	4	2574		
		RP-T8-4FT-3L-8XX-10V-M-G2-18W	3	4	2574		
20W	T5	RP-T5-2FT-2L-8XX-10V-M-G2-20W	2	2	2640		
		RP-T5-2FT-3L-8XX-10V-M-G2-20W	3	2	2640		
		RP-T5-2FT-4L-8XX-10V-M-G2-20W	4	2	2640		
		RP-T5-3FT-2L-8XX-10V-M-G2-20W	2	3	2640		
		RP-T5-3FT-3L-8XX-10V-M-G2-20W	3	3	2640		
		RP-T5-3FT-4L-8XX-10V-M-G2-20W	4	3	2640		
		RP-T5-4FT-1L-8XX-10V-M-G2-20W	1	4	2820		
		RP-T5-4FT-2L-8XX-10V-M-G2-20W	2	4	2820		
	T8	RP-T5-4FT-3L-8XX-10V-M-G2-20W	3	4	2820		
		RP-T8-2FT-2L-8XX-10V-M-G2-20W	2	2	2880		
		RP-T8-2FT-3L-8XX-10V-M-G2-20W	3	2	2880		
		RP-T8-2FT-4L-8XX-10V-M-G2-20W	4	2	2880		
		RP-T8-3FT-2L-8XX-10V-M-G2-20W	2	3	2760		
		RP-T8-3FT-3L-8XX-10V-M-G2-20W	3	3	2760		
		RP-T8-3FT-4L-8XX-10V-M-G2-20W	4	3	2760		
		RP-T8-4FT-1L-8XX-10V-M-G2-20W	1	4	2860		
		RP-T8-4FT-2L-8XX-10V-M-G2-20W	2	4	2860		
		RP-T8-4FT-3L-8XX-10V-M-G2-20W	3	4	2860		
25W	T5	RP-T5-2FT-2L-8XX-10V-M-G2-25W	2	2	3300		
		RP-T5-2FT-3L-8XX-10V-M-G2-25W	3	2	3300		
		RP-T5-2FT-4L-8XX-10V-M-G2-25W	4	2	3300		
		RP-T5-3FT-2L-8XX-10V-M-G2-25W	2	3	3300		
		RP-T5-3FT-3L-8XX-10V-M-G2-25W	3	3	3300		
		RP-T5-3FT-4L-8XX-10V-M-G2-25W	4	3	3300		
		RP-T5-4FT-2L-8XX-10V-M-G2-25W	2	4	3525		
		RP-T5-4FT-3L-8XX-10V-M-G2-25W	3	4	3525		
	T8	RP-T5-4FT-4L-8XX-10V-M-G2-25W	4	4	3525		
		RP-T5HO-4FT-1L-8XX-10V-M-G2-25W	1	4	3525		
		RP-T8-2FT-3L-8XX-10V-M-G2-25W	3	2	3600		
		RP-T8-2FT-4L-8XX-10V-M-G2-25W	4	2	3600		
		RP-T8-3FT-2L-8XX-10V-M-G2-25W	2	3	3450		
		RP-T8-3FT-3L-8XX-10V-M-G2-25W	3	3	3450		
		RP-T8-3FT-4L-8XX-10V-M-G2-25W	4	3	3450		
		RP-T8-4FT-1L-8XX-10V-M-G2-25W	1	4	3575		
		RP-T8-4FT-2L-8XX-10V-M-G2-25W	2	4	3575		
		RP-T8-4FT-3L-8XX-10V-M-G2-25W	3	4	3575		
		RP-T8-4FT-4L-8XX-10V-M-G2-25W	4	4	3575		

*SYSTEM LUMENS is calculated based on 4000K lamp design parameters. Actual lumen output will vary depending on lamp color and driver efficiency based on wattage setting.

C-Flex LUTRON, 0 - 10V, LVD RETROFIT

ORDERING GUIDE FOR T5/T5HO/T8 0-10V KITS ONLY

	PART #	LAMPS PER DRIVER	LAMP LENGTH (FT)	SYSTEM LUMENS*	PERFORMANCE CATEGORY	PREODUCT ID
30W	T5	RP-T5-2FT-3L-8XX-10V-M-G2-30W	3	2	3960	
		RP-T5-2FT-4L-8XX-10V-M-G2-30W	4	2	3960	
		RP-T5-3FT-3L-8XX-10V-M-G2-30W	3	3	3960	
		RP-T5-3FT-4L-8XX-10V-M-G2-30W	4	3	3960	
		RP-T5-4FT-2L-8XX-10V-M-G2-30W	2	4	4230	
		RP-T5-4FT-3L-8XX-10V-M-G2-30W	3	4	4230	
	T8	RP-T5-4FT-4L-8XX-10V-M-G2-30W	4	4	4230	
		RP-T8-2FT-3L-8XX-10V-M-G2-30W	3	2	4320	
		RP-T8-2FT-4L-8XX-10V-M-G2-30W	4	2	4320	
		RP-T8-3FT-3L-8XX-10V-M-G2-30W	3	3	4140	
		RP-T8-3FT-4L-8XX-10V-M-G2-30W	4	3	4140	
		RP-T8-4FT-2L-8XX-10V-M-G2-30W	2	4	4290	
		RP-T8-4FT-3L-8XX-10V-M-G2-30W	3	4	4290	
		RP-T8-4FT-4L-8XX-10V-M-G2-30W	4	4	4290	
35W	T5	RP-T5-2FT-3L-8XX-10V-M-G2-35W	3	2	4620	
		RP-T5-2FT-4L-8XX-10V-M-G2-35W	4	2	4620	
		RP-T5-3FT-3L-8XX-10V-M-G2-35W	3	3	4620	
		RP-T5-3FT-4L-8XX-10V-M-G2-35W	4	3	4620	
		RP-T5-4FT-2L-8XX-10V-M-G2-35W	2	4	4935	
		RP-T5-4FT-3L-8XX-10V-M-G2-35W	3	4	4935	
		RP-T5-4FT-4L-8XX-10V-M-G2-35W	4	4	4935	
		RP-T8-2FT-4L-8XX-10V-M-G2-35W	4	2	5040	
	T8	RP-T8-3FT-3L-8XX-10V-M-G2-35W	3	3	4830	
		RP-T8-3FT-4L-8XX-10V-M-G2-35W	4	3	4830	
		RP-T8-4FT-2L-8XX-10V-M-G2-35W	2	4	5005	
		RP-T8-4FT-3L-8XX-10V-M-G2-35W	3	4	5005	
		RP-T8-4FT-4L-8XX-10V-M-G2-35W	4	4	5005	
40W	T5	RP-T5-2FT-4L-8XX-10V-M-G2-40W	4	2	5280	
		RP-T5-3FT-4L-8XX-10V-M-G2-40W	4	3	5280	
		RP-T5-4FT-2L-8XX-10V-M-G2-40W	2	4	5640	
		RP-T5-4FT-3L-8XX-10V-M-G2-40W	3	4	5640	
		RP-T5-4FT-4L-8XX-10V-M-G2-40W	4	4	5640	
	T8	RP-T8-2FT-4L-8XX-10V-M-G2-40W	4	2	5760	
		RP-T8-3FT-4L-8XX-10V-M-G2-40W	4	3	5520	
		RP-T8-4FT-2L-8XX-10V-M-G2-40W	2	4	5720	
		RP-T8-4FT-3L-8XX-10V-M-G2-40W	3	4	5720	
		RP-T8-4FT-4L-8XX-10V-M-G2-40W	4	4	5720	
45W	T5	RP-T5-2FT-4L-8XX-10V-M-G2-45W	4	2	5940	
		RP-T5-3FT-4L-8XX-10V-M-G2-45W	4	3	5940	
		RP-T5-4FT-3L-8XX-10V-M-G2-45W	3	4	6345	
		RP-T5-4FT-4L-8XX-10V-M-G2-45W	4	4	6345	
	T5HO	RP-T5HO-4FT-2L-8XX-10V-M-G2-45W	2	4	6345	
		RP-T8-3FT-4L-8XX-10V-M-G2-45W	4	3	6210	
	T8	RP-T8-4FT-2L-8XX-10V-M-G2-45W	2	4	6435	
		RP-T8-4FT-3L-8XX-10V-M-G2-45W	3	4	6435	
		RP-T8-4FT-4L-8XX-10V-M-G2-45W	4	4	6435	
		RP-T8-4FT-4L-8XX-10V-M-G2-45W	4	4	6435	

*SYSTEM LUMENS is calculated based on 4000K lamp design parameters. Actual lumen output will vary depending on lamp color and driver efficiency based on wattage setting.



CORPORATE HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949

847.380.3540 • c-flexretrofits.com

01.06.25 Information is subject to change without notice.

The Lutron logo, EcoSystem, and Lutron are trademarks or registered trademarks of Lutron Electronics Co., Inc., in the U.S. and/or other countries.

C-Flex LUTRON, 0 - 10V, LVD RETROFIT

ORDERING GUIDE FOR T5/T5HO/T8 0-10V KITS ONLY

		PART #	LAMPS PER DRIVER	LAMP LENGTH (FT)	SYSTEM LUMENS*	PERFORMANCE CATEGORY	PRODUCT ID
50W	T5	RP-T5-4FT-3L-8XX-10V-M-G2-50W	3	4	7050		
		RP-T5-4FT-4L-8XX-10V-M-G2-50W	4	4	7050		
	T5HO	RP-T5HO-4FT-2L-8XX-10V-M-G2-50W	2	4	7050		
		RP-T8-4FT-2L-8XX-10V-M-G2-50W	2	4	7150		
	T8	RP-T8-4FT-3L-8XX-10V-M-G2-50W	3	4	7150		
		RP-T8-4FT-4L-8XX-10V-M-G2-50W	4	4	7150		
60W	T5	RP-T5-4FT-3L-8XX-10V-M-G2-60W	3	4	8460		
		RP-T5-4FT-4L-8XX-10V-M-G2-60W	4	4	8460		
	T8	RP-T8-4FT-3L-8XX-10V-M-G2-60W	3	4	8580		
		RP-T8-4FT-4L-8XX-10V-M-G2-60W	4	4	8580		
70W	T5	RP-T5-4FT-3L-8XX-10V-M-G2-70W	3	4	9870		
		RP-T5-4FT-4L-8XX-10V-M-G2-70W	4	4	9870		
	T8	RP-T8-4FT-3L-8XX-10V-M-G2-70W	3	4	10010		
		RP-T8-4FT-4L-8XX-10V-M-G2-70W	4	4	10010		
80W	T5	RP-T5-4FT-4L-8XX-10V-M-G2-80W	3	4	11280		
		RP-T5HO-4FT-3L-8XX-10V-M-G2-80W	4	4	11280		
	T8	RP-T8-4FT-3L-8XX-10V-M-G2-80W	3	4	11440		
		RP-T8-4FT-4L-8XX-10V-M-G2-80W	4	4	11440		

CAUTION! MAX WATTAGES PER LEDBAR
 1FT: 7.5W 2FT: 12.5W 3FT: 12.5W 4FT: 25W

ORDERING GUIDE FOR BAR 0-10V KITS ONLY

		PART #	BAR PER DRIVER	BAR LENGTH (FT)	SYSTEM LUMENS*
6W		RP-BAR-2FT-1L-8XX-10V-M-G2-6W	1	2	936
		RP-BAR-3FT-1L-8XX-10V-M-G2-6W	1	3	894
		RP-BAR-4FT-1L-8XX-10V-M-G2-6W	1	4	756
8W		RP-BAR-2FT-1L-8XX-10V-M-G2-8W	1	2	1288
		RP-BAR-3FT-1L-8XX-10V-M-G2-8W	1	3	1264
		RP-BAR-4FT-1L-8XX-10V-M-G2-8W	1	4	1232
10W		RP-BAR-2FT-1L-8XX-10V-M-G2-10W	1	2	1640
		RP-BAR-2FT-2L-8XX-10V-M-G2-10W	2	2	1440
		RP-BAR-2FT-3L-8XX-10V-M-G2-10W	3	2	1162
		RP-BAR-3FT-1L-8XX-10V-M-G2-10W	1	3	1640
		RP-BAR-4FT-1L-8XX-10V-M-G2-10W	1	4	1630
12W		RP-BAR-2FT-1L-8XX-10V-M-G2-12W	1	2	1968
		RP-BAR-2FT-2L-8XX-10V-M-G2-12W	2	2	1728
		RP-BAR-2FT-3L-8XX-10V-M-G2-12W	3	2	1728
		RP-BAR-3FT-1L-8XX-10V-M-G2-12W	1	3	1992
		RP-BAR-3FT-2L-8XX-10V-M-G2-12W	2	3	1788
		RP-BAR-4FT-1L-8XX-10V-M-G2-12W	1	4	1956
		RP-BAR-4FT-2L-8XX-10V-M-G2-12W	2	4	1848

*SYSTEM LUMENS is calculated based on 4000K lamp design parameters. Actual lumen output will vary depending on lamp color and driver efficiency based on wattage setting.



CORPORATE HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
 INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949

847.380.3540 • c-flexretrofits.com

01.06.25 Information is subject to change without notice.

The Lutron logo, EcoSystem, and Lutron are trademarks or registered trademarks of Lutron Electronics Co., Inc., in the U.S. and/or other countries.

ORDERING GUIDE FOR BAR 0-10V KITS ONLY

	PART #	BARS PER DRIVER	BAR LENGTH (FT)	SYSTEM LUMENS*	DLC CATEGORY	3500K	4000K	5000K
15W	RP-BAR-2FT-2L-8XX-10V-M-G2-15W	2	2	2340				
	RP-BAR-2FT-3L-8XX-10V-M-G2-15W	3	2	2160				
	RP-BAR-3FT-1L-8XX-10V-M-G2-15W	1	2	2505				
	RP-BAR-3FT-2L-8XX-10V-M-G2-15W	2	3	2370				
	RP-BAR-3FT-3L-8XX-10V-M-G2-15W	3	3	2235				
	RP-BAR-4FT-1L-8XX-10V-M-G2-15W	1	4	2505				
	RP-BAR-4FT-2L-8XX-10V-M-G2-15W	2	4	2310				
18W	RP-BAR-2FT-2L-8XX-10V-M-G2-18W	2	2	2898				
	RP-BAR-2FT-3L-8XX-10V-M-G2-18W	3	2	2592				
	RP-BAR-2FT-4L-8XX-10V-M-G2-18W	4	2	2592				
	RP-BAR-3FT-2L-8XX-10V-M-G2-18W	2	3	2844				
	RP-BAR-3FT-3L-8XX-10V-M-G2-18W	3	3	2682				
	RP-BAR-3FT-4L-8XX-10V-M-G2-18W	4	3	2682				
	RP-BAR-4FT-1L-8XX-10V-M-G2-18W	1	4	3024				
	RP-BAR-4FT-2L-8XX-10V-M-G2-18W	2	4	2934				
	RP-BAR-4FT-3L-8XX-10V-M-G2-18W	3	4	2772				
20W	RP-BAR-2FT-2L-8XX-10V-M-G2-20W	2	2	3220				
	RP-BAR-2FT-3L-8XX-10V-M-G2-20W	3	2	2880				
	RP-BAR-2FT-4L-8XX-10V-M-G2-20W	4	2	2880				
	RP-BAR-3FT-2L-8XX-10V-M-G2-20W	2	3	3280				
	RP-BAR-3FT-3L-8XX-10V-M-G2-20W	3	3	3160				
	RP-BAR-3FT-4L-8XX-10V-M-G2-20W	4	3	3160				
	RP-BAR-4FT-1L-8XX-10V-M-G2-20W	1	4	3360				
	RP-BAR-4FT-2L-8XX-10V-M-G2-20W	2	4	3260				
	RP-BAR-4FT-3L-8XX-10V-M-G2-20W	3	4	3080				
25W	RP-BAR-2FT-2L-8XX-10V-M-G2-25W	2	2	4100				
	RP-BAR-2FT-3L-8XX-10V-M-G2-25W	3	2	4025				
	RP-BAR-2FT-4L-8XX-10V-M-G2-25W	4	2	3900				
	RP-BAR-3FT-3L-8XX-10V-M-G2-25W	3	3	4100				
	RP-BAR-3FT-4L-8XX-10V-M-G2-25W	4	3	3950				
	RP-BAR-4FT-1L-8XX-10V-M-G2-25W	1	4	4175				
	RP-BAR-4FT-2L-8XX-10V-M-G2-25W	2	4	4175				
	RP-BAR-4FT-3L-8XX-10V-M-G2-25W	3	4	3850				
	RP-BAR-4FT-4L-8XX-10V-M-G2-25W	4	4	3850				
30W	RP-BAR-2FT-3L-8XX-10V-M-G2-30W	3	2	4920				
	RP-BAR-2FT-4L-8XX-10V-M-G2-30W	4	2	4830				
	RP-BAR-3FT-3L-8XX-10V-M-G2-30W	3	3	4980				
	RP-BAR-3FT-4L-8XX-10V-M-G2-30W	4	3	4740				
	RP-BAR-4FT-2L-8XX-10V-M-G2-30W	2	4	5040				
	RP-BAR-4FT-3L-8XX-10V-M-G2-30W	3	4	4890				
	RP-BAR-4FT-4L-8XX-10V-M-G2-30W	4	4	4620				
35W	RP-BAR-2FT-3L-8XX-10V-M-G2-35W	3	2	5740				
	RP-BAR-2FT-4L-8XX-10V-M-G2-35W	4	2	5635				
	RP-BAR-3FT-3L-8XX-10V-M-G2-35W	3	3	5810				
	RP-BAR-3FT-4L-8XX-10V-M-G2-35W	4	3	5740				
	RP-BAR-4FT-2L-8XX-10V-M-G2-35W	2	4	5880				
	RP-BAR-4FT-3L-8XX-10V-M-G2-35W	3	4	5705				
	RP-BAR-4FT-4L-8XX-10V-M-G2-35W	4	4	5390				
40W	RP-BAR-2FT-4L-8XX-10V-M-G2-40W	4	2	6560				
	RP-BAR-3FT-4L-8XX-10V-M-G2-40W	4	3	6560				
	RP-BAR-4FT-2L-8XX-10V-M-G2-40W	2	4	6680				
	RP-BAR-4FT-3L-8XX-10V-M-G2-40W	3	4	6680				
	RP-BAR-4FT-4L-8XX-10V-M-G2-40W	4	4	6520				

*SYSTEM LUMENS is calculated based on 4000K lamp design parameters. Actual lumen output will vary depending on lamp color and driver efficiency based on wattage setting.

C-Flex LUTRON, 0 - 10V, LVD RETROFIT




ORDERING GUIDE FOR BAR 0-10V KITS ONLY

	PART #	BARS PER DRIVER	BAR LENGTH (FT)	SYSTEM LUMENS*	DLC CATEGORY	3500K	4000K	5000K
45W	RP-BAR-2FT-4L-8XX-10V-M-G2-45W	4	2	7380				
	RP-BAR-3FT-4L-8XX-10V-M-G2-45W	4	3	7470				
	RP-BAR-4FT-2L-8XX-10V-M-G2-45W	2	4	7425				
	RP-BAR-4FT-3L-8XX-10V-M-G2-45W	3	4	7515				
	RP-BAR-4FT-4L-8XX-10V-M-G2-45W	4	4	7335				
50W	RP-BAR-4FT-2L-8XX-10V-M-G2-50W	2	4	8200				
	RP-BAR-4FT-3L-8XX-10V-M-G2-50W	3	4	8400				
	RP-BAR-4FT-4L-8XX-10V-M-G2-50W	4	4	8400				
60W	RP-BAR-4FT-3L-8XX-10V-M-G2-60W	3	4	10,080				
	RP-BAR-4FT-4L-8XX-10V-M-G2-60W	4	4	10,080				
70W	RP-BAR-4FT-3L-8XX-10V-M-G2-70W	3	4	11,690				
	RP-BAR-4FT-4L-8XX-10V-M-G2-70W	4	4	11,760				
70W	RP-BAR-4FT-4L-8XX-10V-M-G2-80W	4	4	13,360				


*SYSTEM LUMENS is calculated based on 4000K lamp design parameters. Actual lumen output will vary depending on lamp color and driver efficiency based on wattage setting.

DRIVER DIMENSIONS

0-10V Driver Dimensions - (Standard M Case Driver. Contact us for K/KN case options.)



Lutron Driver Dimensions




Case type K
3.00 in (76 mm) W x 1.00 in (25 mm) H x 4.90 in (124 mm) L




Case type M
1.18 in (30 mm) W x 1.00 in (25 mm) H x 14.25 in (362 mm) L

K Case Connector Locations




KN Case Side Entry Connector Locations



LVD Driver Dimensions




M Case
4.07" L X 1.03" W X 0.94" H




K Case
4.07" L X 1.03" W X 0.94" H

Note: LVD M and K case driver options are not available for 1-lamp 26W and 32W fluorescent CFL replacement kits. It is important that LVD drivers are mounted to a flat metal surface in order to maximize service life.

KN Case 25W System Max



KN Case 26W to 60W System Wattage



C-Flex

CORPORATE HEADQUARTERS 188 S. Northwest Highway • Cary, IL 60013
INNOVATION & MANUFACTURING CENTER 30 Log Bridge Road, Building 200 • Middleton, MA 01949

847.380.3540 • c-flexretrofits.com

01.06.25 Information is subject to change without notice.

The Lutron logo, EcoSystem, and Lutron are trademarks or registered trademarks of Lutron Electronics Co., Inc., in the U.S. and/or other countries.