

S25 36IN/18GA/ULSF2



Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

Product datasheet

Technical data

General product information

Product Number	69783
Product Name	S2536IN18GAULSF2 100/CS 20/SKU
Ordering Abbreviation	S25 36IN/18GA/ULSF2
Brand Name	OSRAM
General Description	S25, SOCKET, LAMPHOLDER
CSA File No.	LR20904

Electrical data

Maximum Wattage (W)	1000 W
Maximum Voltage (V)	250 V

Physical attributes

Length (in)	1.53 in
Length (mm)	38.9 mm
Width (in)	0.93 in
Width (mm)	23.6 mm
Height (in)	1.06 in
Height (mm)	26.8 mm
Body Material	Ceramic Steatite
Contact Material	Nickel Plated Brass
Wire Type	SF2
Wire Gauge (AWG)	18 AWG
Wire Color(s)	WHITE/BLACK
Lead Length (in)	36 in
Lead Length (mm)	914 mm
Lead Strip Length (in)	0.375 in
Lead Strip Length (mm)	9 mm

Additional product data

Lamp Base Reference	E11
Maximum Operating Temperature (°C)	200 C
Rohs Compliant	Yes
Underwriters Laboratories File No.	E31557

Packaging Information

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
69783	4008321534354	Shipping box (Case)	20	10.1 in x 7.4 in x 2.4 in	2.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.