

S26




Specifications:

Maximum Wattage	3000 W
Maximum Voltage	600 V
Maximum Operating Temperature	350° C
Qualifications	UL Recognized – E31557 CSA Certified – LR20904
Body Material	Steatite / Aluminum / Plated Steel
Contact Material	Silver Plated Brass
Wire Leads	AWG 16/14, 600 V/200° C minimum
Lamp Types	Halogen and Discharge

LAMP BASE:

Recessed Single Contact
(RSC) R7 & RX7



ORDERING INFORMATION

Product Number	Product Description	Wire Gauge/Type/Color	Wire Length (inches)	Case / SKU Qty Qty
69676	S26 12IN/14GA/UL1659	AWG14/UL1659/White	12	100 / 100
69673	S26 12IN/16GA/ULSF2	AWG16/ULSF2/Black	12	100 / 100
69674	S26 13IN/16GA/ULSF2	AWG16/ULSF2/Black	13	100 / 100
69680	S26 18IN/16GA/ULSF2	AWG16/ULSF2/Black	18	100 / 100
69684	S26 19IN/16GA/UL5359	AWG16/UL5359/Natural	19	100 / 100
69686	S26 22IN/16GA/UL1659	AWG16/UL1659/Black	22	100 / 100
69675	S26 26IN/16GA/ULSF2	AWG16/ULSF2/Black	26	100 / 100
69012*	S26 36IN/16GA/ULSF2	AWG16/ULSF2/White	36	100 / 20
69678	S26 36IN/16GA/ULSF2	AWG16/ULSF2/White	36	100 / 100
69677	S26 42IN/14GA/UL1659	AWG14/UL1659/White	42	100 / 100
69685	S26 42IN/14GA/UL5359	AWG14/UL5359/Blue	42	100 / 100
69682	S26 44IN/14GA/UL5359	AWG14/UL5359/Natural	44	100 / 100
69679	S26 48IN/14GA/UL1659	AWG14/UL1659/White	48	100 / 100
69683	S26 48IN/14GA/ULSF2	AWG14/ULSF2/Black	48	100 / 100
69681	S26 56IN/14GA/UL5359	AWG14/UL5359/Natural	56	100 / 100

*Included in Stocking Program. Other types are made-to-order.

