

## S26A 18IN/16GA/ULSF2



### Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

### Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

## Product datasheet

---

### Technical data

#### General product information

Product Number	69011
Product Name	S26A18IN16GAULSF2 100/CS 20/SKU
Ordering Abbreviation	S26A 18IN/16GA/ULSF2
Brand Name	OSRAM
General Description	S26A Socket AWG16 SF2 (URC)
CSA File No.	LR20904
Old Part Number	F592500

#### Electrical data

Maximum Wattage (W)	3000 W
Maximum Voltage (V)	600 V

#### Physical attributes

Length (in)	1.562 in
Length (mm)	39.7 mm
Width (in)	0.968 in
Width (mm)	24.6 mm
Height (in)	1.48 in
Height (mm)	37.6 mm
Body Material	Ceramic Steatite/Aluminum/Plated Steel
Contact Material	Silver Plated Brass
Wire Type	SF2
Wire Gauge (AWG)	16 AWG
Wire Color(s)	Black
Lead Length (in)	18 in
Lead Length (mm)	457 mm
Lead Strip Length (in)	0.25 in
Lead Strip Length (mm)	6 mm

#### Additional product data

Lamp Base Reference	R7s, RX7s Recessed Single Contact (RSC)
Maximum Operating Temperature (°C)	200 C
Rohs Compliant	Yes
Underwriters Laboratories File No.	E31557

---

### Packaging Information

## Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
69011	4008321388674	Shipping box (Case)	20	10.1 in x 7.4 in x 2.4 in	1.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.