

## 10W 0-10V 'Dim to Dark' LED Driver

### SOLOdrive

SOLOdrive offers industry-best Natural Dimming to dark - LED dimming made beautiful! With any dimmer, in any application. Symbiosis on SOLOdrive stands for unity, for the SOLOdrive working seamlessly together with LED modules, controls and intelligent luminaire elements.

### Product offering



### SOLOdrive 161/B

Part number (P/N)	SL0161B3
Product description	SOLOdrive, 10W, 0-10V, 1 control channel, constant current, 1x 55V output, bottom feed, metal square


### Features & benefits

Natural dimming	Dim to dark, smooth brightness changes, excellent flicker performance, adaptable dimming curves, configurable minimum dimming level.
LEDcode	Configurable design to work with most constant current LED modules and arrays, while providing a connection point to integrated peripheral controls.
Programmable	Fine-tune your driver for any application
Performance	Universal input voltage range, low inrush current and total harmonic distortion (THD), high power factor and efficiency
Camera compatibility	Hybrid HydraDrive technology is proven to work in TV studios and security camera environments

Project name:	Contact details:
Project number:	
LED driver order number:	

### Typical flicker performance

Typical flicker percent as a function of frequency, measured across the dimming range. The results are overlaid with the low-risk (yellow) and no observable effect (green) levels as defined in IEEE P1789.



### Electrical Specifications

Driver type	Constant current
Number of LED outputs	1 (UL Class2)
Maximum LED output power	10W
Programmable LED output current range	150 - 1400mA
Maximum input current AC	0.1A @ 120V 0.06A @ 230V 0.05A @ 277V
LED output type	Programmable in 1mA increments within specified current range
LED output voltage range	2 - 55V
Nominal input voltage range AC	120 - 250V (ENEC), 120 - 277V (UL)
Nominal input voltage range DC	120 - 250V
Control protocol	0+10V  LEDcode
Control Channels	1

### Certifications



## Warranty

Warranty period [General Terms and Conditions](#)


## Dimensions, weight, packaging

Length (L)	500 mm / 19.7 in
Width (W)	310 mm / 12.2 in
Height (H)	190 mm / 7.5 in
Weight	11.1 kg
Products per box	40 pcs

## Connector layout



## Order number configurator



P/N LED driver part number

LED output current Enter value in 1mA increments, e.g. "811" for 811mA

Dimming curve  
 "LOG" for logarithmic (default)  
 "LIN" for linear  
 "SLN" for soft-linear  
 "SQU" for square

Minimum dimming level Leave blank for default minimum dimming level of 0.1%. Specify in 0.1% increments, e.g. "10.5" for 10.5%.

---

#### **Europe, Rest of World**

eldoLED B.V.  
Science Park Eindhoven 5125  
5692 ED Son  
The Netherlands

E: [info@eldoled.com](mailto:info@eldoled.com)  
W: [www.eldoled.com](http://www.eldoled.com)

#### **North America**

eldoLED America  
One Lithonia Way  
Conyers, GA 30012  
USA

E: [info@eldoled.com](mailto:info@eldoled.com)  
W: [www.eldoled.com](http://www.eldoled.com)

---