




SLED300W

300W Programmable LED Drivers



Electrical Specifications

Maximum Power:	300W
Typical Efficiency:	90%
Input Voltage Range:	120-277 Vac Nom. (108-305 V Min/Max)
Frequency:	50/60 Hz Nom. (47-63 Hz Min/Max)
Power Factor:	≥ 0.90 @ ≥ 50% Load, 120Vac-277Vac
Inrush Current:	≤ 118A at 25C, 120Vac, cold start, Max. Load
Input Current (Max):	2.86A Maximum @ 120Vac
Output Dimming Range:	1-100% with adjustable minimum, Dim to Zero YES/NO
Load Regulation:	±3%
Line Regulation:	±2%
THD:	≤ 20% at 120/230/277Vac ≥ 50% Load
Start-up Time:	<500ms @ 100% Load
Output Ripple Current:	≤ 5% Io



Protections

Over-voltage:	No Damage, Auto Recovery after fault is removed
Over-current:	Auto recovery, Current limiting circuit
Short Circuit:	No Damage, Auto Recovery after fault is removed
Over-temperature:	Current Foldback at TC ≥ 95°C, OFF @ Tc ~ 100°C

Environmental Specifications

Max Case Life Temp: (5 year warranty)	85°C
Maximum Case Temp (UL):	90°C
Minimum Starting Temp:	-40°C
Storage Temperature:	-40°C to +85°C
Humidity:	Up to 95% RH
Cooling:	Convection
Vibration Frequency:	5 to 55 Hz/2g, 30 minutes
Sound Rating:	Class A
EMC:	FCC 47CFR Part 15, Class B @ 120Vac, Class A @ 277Vac compliant
Weight:	1630 grams (57.5 oz)

- 0-10V Class 2 Isolated Dimming Circuit
- Dim+ Violet/Dim- Pink are Class 2 Isolated from all other inputs and outputs
- 0-10Vdc Dimming Suitable for Class1 or Class 2 Circuit Program driver with GUI software for fast setup
- Program driver with GUI software for fast setup
- Linear or logarithmic dimming curve options
- Flicker free output for comfort and critical applications
- 2-stage power supply design for better performance over wide range of outputs
- Auxiliary 12Vdc, 200mA output for powering controls or fans
- NTC option allows for thermal protection of LED engine
- Programmable Output Current (POC): 200-6700mA
- UL Class P, Dry & Damp Location Rated
- Dim to zero with programmable YES/NO
- Metal housing
- 0-10V Dim to 1%, programmable min dim
- Soft Start YES/NO (Default = NO)
- End of Life Indicator (Default = Disabled)
- Constant Lumen Lookup Table (Default = Disabled)

Model Table

Part	Model	Adj. Current Out (mA +5%)	Voltage Out (Vdc)	Max Power (W)	Default Current
93309791	SLED300W-55-C6700	1000-6700	10-55	300	6700
93309792	SLED300W-100-C4300	700-4300	20-100	300	4300
93309793	SLED300W-200-C3000	500-3000	36-200	300	3000
93309794	SLED300W-457-C1400	200-1400	83-457	300	1400
93309808	SLED300W-55-C6700-NFC	1000-6700	10-55	300	6700
93309809	SLED300W-100-C4300-NFC	700-4300	20-100	300	4300
93309810	SLED300W-200-C3000-NFC	500-3000	36-200	300	3000
93309811	SLED300W-457-C1400-NFC	200-1400	83-457	300	1400

Safety Cert. Standard


UL/CUL	UL8750, UL1310 for UL Class 2 & CAN/CSA C22.2 No. 250.13, UL Class P
CE	EN61347-1, EN61347-2-13

EMC Standard Notes


FCC, 47CFR Part 15	Class B @ 120Vac, Class A @ 277Vac
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment.
EN 61000-3-2	Part 3-2: Limits for harmonic current emissions Class C, ≥80% Rated Power
EN 61000-3-3	Part 3-3: Limitation of voltage changes, voltage fluctuations and flicker
EN 61000-4-5	Part 4-5: Surge Immunity test, 2 kV L-N, 4 kV L-FG & N-FG
Energy Star	Energy Star transient protection: Ballast or driver shall comply with ANSI/IEEE C62.41.1-2002 and ANSI/IEEE C62.41.2-2002, Category A operation. The line transient shall consist of seven strikes of a 100 kHz ring wave, 2.5 kV level, for both common mode and differential mode.

Dimensions

RD: Wire Programmable Version with NTC



RDNFC: NFC Wireless Programmable Version with NTC




LED wiring distance:

Recommended maximum wiring distance:
44.76V@6700mA with ~5% Vout Drop.

AWG	#22	#21	#20	#19	#18	#16
Distance (m)	3.2	4.0	5.0	6.3	8.0	12.7
Distance (ft)	10.3	13.0	16.5	20.7	26.2	41.6

Soft Start Operation

Specification: Time-To-First-Light (100mA) <500ms, Time to 90% Iout ~ 3 Seconds, Time to 100% Iout <4.0 Seconds







LED wiring distance:

Recommended maximum wiring distance:
21.43V@1400mA with ~5% Vout Drop.

AWG	#22	#21	#20	#19	#18	#16
Distance (m)	7.2	9.1	11.5	14.5	18.3	29.0
Distance (ft)	23.7	29.9	37.7	47.5	59.9	95.3

Power Characteristics




Programmable Parameter Defaults

Parameter	Default Setting	Setting Range
Output Current (mA)	See model table	See model table
Dim to Zero	No	Yes or No
Minimum Dim Level (%)	1	1 - 100
Dimming Curve	Linear	Linear or Logarithmic
NTC Maximum Ohms (kΩ)	6.3	2 - 10
NTC Minimum Ohms (kΩ) *1	2	1 - 10
NTC-Minimum Output Level (%)	10	1 - 100
Disable Dimming	No	Yes or No
Soft Start	No	Yes or No
End of Life Indicator	Disabled	1k to 245k Hour
Constant Lumen Output Lookup Table	Disabled	1k Hours/50% lout to 254k Hours/100% lout, Max 8 entry lookup table


*1 Note: NTC Minimum value must not exceed 70% of Maximum value

Note: The area under the life-temperature curve represents where the driver has highly reliable operation within specification. Driver performance may drift out of published specifications as the hours of operation exceed the curve at a given temperature. Higher operating temperatures increase the chances of a failure to function. Other electrical, mechanical and environmental factors affect driver lifetime but are not represented in this calculation.

Wiring



Power Operating Window




Labeling Programmable Drivers

It is highly recommended that the drivers be labeled with information traceable to the programming profile. It can include the programmed output current, dimming curve type, minimum dimming level and name of the file storing the profile.

This information is critical to answering any field questions from the contractor or end user.

Programming Guide


Refer to the SelectSYNC Programming Software User's Manual.




Dimming: 0-10Vdc

Parameter	Minimum	Typical	Maximum
12V Auxiliary Output	11.0V	12.0V	13.0V
12V Auxiliary Output Source Current	0mA		200mA
Absolute Voltage Range on 0-10V Input (Purple Wire)	-2.0V		+15V
Source Current out of 0-10V Input (Purple Wire)	0uA		250uA


Typical Dimming Circuit: 2-Wire Resistance



Typical Dimming Circuit: 2-Wire 0-10V Analog



% Output Current Vs. 0-10V DC Dimming Input



0-10V Dimming Notes:


1. Part comes with DIM+, DIM-, SCOM & +12V auxiliary connectors. +12V return is connected to COM. This is for controls and sensors that need a 12V supply.
2. Part is compatible with most 0-10V Wall Slide dimmers and direct 0-10V analog signal. Recommended dimmer is Leviton IP710 or equivalent connected between DIM + and DIM- wires.
3. Output current will be Minimum Programmed Value when $V_{dim} \leq 1.00V$. Dim to Zero YES/NO.
4. Output will be 100% with DIM+/DIM- open or above 9.0V and Minimum Programmed Value with DIM+/DIM- Shorted.
5. Minimum dimming level is programmable with TRP Programming software.

NTC Information

Module Temperature Protection using External NTC (Negative Temperature Coefficient)

Select a Negative Thermal Coefficient (NTC) resistor with a resistance range that allows the full output current to flow at safe LED operating temperatures. NTC resistance should drop sufficiently to allow reduced output current at elevated or harmful LED temperature levels. NTC operation should be thoroughly tested to ensure proper operation over all the full temperature range of the Driver and the LED Engine.

Example: NTC High, NTC Low and NTC Minimum Iout% can be programmed using TRP Programmer USB interface & TRP PC based GUI Software. Factory Default Settings: NTC Low = 2.0K ~ 10% Iout, NTC High = 6.3K, 100% Iout
 Programmable settings: NTC Minimum Level (%), NTC Minimum Ohms, NTC Maximum Ohms.



Module Temperature Protection Example

NTC = 805SMD, $R_{25C} = 15K \text{ Ohm} \pm 2\%$, $R_{64C} = 3700$, Vishay Part #: NTCS0805E3153GMT
 With part set: NTC Max = 6.3K, NTC MIN = 2.0K, Iout Min = 10%

