

VPL50-xxx-MVHDA-PD-1c	
Driver Type	Constant Current LED Driver
No. of Channels	
Input Voltage	120-277 V
Input Frequency	50-60 Hz
Dimming	ProDim:



Features
<ul style="list-style-type: none"> • Universal Voltage (120-277V) • Multiple Output Channels • Constant Current • Programmable Wattage and Drive Current • ProDim: • Integrates with Adaptive Lighting Control Systems • Compatible with LED modules and Coretech LED tubes • UL, cUL, UL8750 Class 2 • FCC Part 15 Class A



CoreTech VPL

PRODUCT SPECIFICATIONS

OUTPUT	INPUT
No. of Channels	Frequency
No. of Coretech LED Lamps	Input Voltage (range)
Output Voltage (Range)	Power Factor (min.)
Output Current Range (Programmable @ full load)	THD (max.)
Total Rated Power	Efficiency (typical)

Wiring diagram

Dimension

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.

Espen Technology, Inc. | 12257 Florence Avenue | Santa Fe Springs, CA 90670 | Phone: (562) 529-2938 | Fax: (562) 529-2978
Toll Free: (866) 933-7736 | Email: info@espentech.com | www.espentech.com