



SPECIFICATION SHEET : WH3-120-C

This Is An Original Product From Fulham Co., Inc



**Description : WorkHorse Series Versatile, Solid State Electronic Ballast.
High Power Factor, Light Weight, Also Available In 77V 50/60 Hz.**

This Ballast Will Operate Following Lamps.

REFER TO LAMP WATTS/TYPE

ELECTRICAL DATA

INPUT VOLT: 120V ± 10%, 50/60Hz								
LAMP WATTS/TYPE	T5CR40W	CR32W	T9CR22+T9CR32 CR	F24T5	F54T5	CFTR42W	F15T8	F15T8
LAMPS OPERATED	1						2	3
INPUT WATTS	36	28	36	25	56	42	28	40
LINE CURRENT:	0.33	0.25	0.32	0.23	0.50	0.37	0.25	0.35
POWER FACTOR	0.93	0.93	0.93	0.92	0.94	0.93	0.92	0.93
BALLAST FACTOR	0.79	0.89	0.69	0.93	0.92	0.83	0.91	0.89
EFFICACY FACTOR	2.16	3.20	1.94	3.70	1.64	2.00	3.28	2.25
THD	38%	39%	37%	41%	34%	38%	39%	36%
EMI/RFI COMPLIANCE	FCC PART 18-A (Non-Consumer)							
SOUND RATING	" A "							
BALLAST TYPE	INSTANT START							
VOLTAGE TRANSIENTS	ANSI 62.41							
INPUT/PROTECTION	FUSE							
MIN. OPERATING TEMP	-30 °C (-20 °F)							
MAX. CASE TEMP	70 °C (158 °F)							
ENERGY STAR 4.0	-							
APPROVALS/CLASS	UL /cUL LISTED, CLASS " P ", 1 OR 2 OUTDOOR							



Fulham Co., Inc extends limited warranty only to the original purchaser or to the first user for the period of 5 years from the date of manufacture as indicated by the date code stamped on each product and when properly installed and under normal conditions of use. For additional warranty guide line, please refer to our Complete Product Catalog OR call Customer Service at 1-323-599-5000.

DUE TO A PROGRAM OF CONTINUOUS IMPROVEMENT, FULHAM Co., INC RESERVES THE RIGHT TO MAKE ANY VARIATION IN DESIGN OR CONSTRUCTION TO THE EQUIPMENT DESCRIBED.

Address : 12705 South Van Ness Ave., Hawthorne, CA 90250 Tel.: 1-323-599-5000, Fax.: 1-323-754-9060. Website: www.fulham.com 2006-21SP-1 rev B



SPECIFICATION SHEET : WH3-120-C

This Is An Original Product From Fulham Co., Inc



**Description : WorkHorse Series Versatile, Solid State Electronic Ballast.
High Power Factor, Light Weight, Also Available In 77V 50/60 Hz.**

This Ballast Will Operate Following Lamps.

REFER TO LAMP WATTS/TYPE

ELECTRICAL DATA

INPUT VOLT: 120V ± 10%, 50/60Hz								
LAMP WATTS/TYPE	FT24W	FT36W	FT40W	T5CR55W	CFQ26W	F32T8	F60T8HO	-
LAMPS OPERATED	1				2	1	1	
INPUT WATTS	24	31	41	53	45	38	61	
LINE CURRENT:	0.22	0.28	0.37	0.47	0.93	0.34	0.54	
POWER FACTOR	0.91	0.92	0.93	0.93	0.93	0.93	0.94	
BALLAST FACTOR	0.91	0.81	0.90	0.86	0.85	1.18	1.10	
EFFICACY FACTOR	3.75	2.65	2.18	1.62	1.88	3.10	1.80	
THD	41%	40%	37%	36%	30%	36%	34%	
EMI/RFI COMPLIANCE	FCC PART 18-A (Non-Consumer)							
SOUND RATING	" A "							
BALLAST TYPE	INSTANT START							
VOLTAGE TRANSIENTS	ANSI 62.41							
INPUT/PROTECTION	FUSE							
MIN. OPERATING TEMP	-30 °C (-20 °F)							
MAX. CASE TEMP	70 °C (158 °F)							
ENERGY STAR 4.0	-							
APPROVALS/CLASS	UL /cUL LISTED, CLASS " P ", 1 OR 2 OUTDOOR							



Fulham Co., Inc extends limited warranty only to the original purchaser or to the first user for the period of 5 years from the date of manufacture as indicated by the date code stamped on each product and when properly installed and under normal conditions of use. For additional warranty guide line, please refer to our Complete Product Catalog OR call Customer Service at 1-323-599-5000.

DUE TO A PROGRAM OF CONTINUOUS IMPROVEMENT, FULHAM Co., INC RESERVES THE RIGHT TO MAKE ANY VARIATION IN DESIGN OR CONSTRUCTION TO THE EQUIPMENT DESCRIBED.

Address : 12705 South Van Ness Ave., Hawthorne, CA 90250 Tel.: 1-323-599-5000, Fax.: 1-323-754-9060. Website: www.fulham.com 2006-21SP-2 rev B