

## XBO 3000W/H XL 1/CS 1/SKU



---

### Product features and benefits

- High luminance for brighter screen illumination
- Consistent performance with constant 6000 K color temperature
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart
- Long lamp life with eXtreme Life technology

---

### Areas of application

- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

# Product datasheet

## Technical data

### General Product Information

Product number (Americas)	69478
Product name (Americas)	XBO 3000W/H XL 1/CS 1/SKU
Global order reference	XBO 3000 W/H XL OFR

### Electrical Data


Nominal wattage	3000 W
Nominal voltage	28 V
Nominal current	105 A
Current control range	70...110 A

### Photometric Data

Luminance	85000 cd/cm <sup>2</sup> <sup>1)</sup>
Light center length (LCL)	167.5 mm

<sup>1)</sup> Measured in the vertical burning position

### Physical Attributes & Dimensions



Electrode gap (cold)	6.0 mm
Base (anode)	SFaX30-13
Base (cathode)	SFaX30-14
Diameter (in)	2.362 in
Diameter	66.0 mm
Length	428.0 mm
Length with base excl. base pins/connection	382.00 mm
Connector: presence	Yes
Product weight	687.00 g

## Product datasheet

### Operating Conditions

<b>Burning position</b>	s30/p30 <sup>1)</sup>
<b>Cooling</b>	Forced <sup>2)</sup>
<b>Max. permitted ambient temp. pinch point</b>	230 °C

<sup>1)</sup> For vertical burning position: anode (+) on top

<sup>2)</sup> Vertical and horizontal

### Lifetime Data

<b>Nominal lifetime</b>	2200 hr
<b>Warranty hours</b>	2200 hrs

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
<b>Primary article identifier</b>	4008321226174
<b>Declaration no. in SCIP database</b>	57f4a7ba-4fa1-44ab-8b28-00f5e4847066
<b>Candidate list substance 1</b>	Lead
<b>CAS No. of substance 1</b>	7439-92-1
<b>Safe use instruction</b>	The identification of the Candidate List substance is sufficient to allow safe use of the article.

### Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

### Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69478	4008321226174	SHIPPING BOX	1	23.2 in x 9.2 in x 9.0 in	3.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.