

Project		Catalog #		Type	
Prepared by		Notes		Date	



AtLite

XLA2, XLN2

The XL exit is a New York City approved, architectural grade die cast, UL 924 code compliant product designed to operate for a minimum of 90 minutes during a power outage.

Typical Applications

Office • Education • Healthcare • Hospitality • Retail


Interactive Menu

- Order Information page 2
- Product Warranty

Product Certification



Dimensional and Mounting Details



Order Information

SAMPLE ORDER NUMBER: **XLA2-8DR1-ES-WW**

Series	Letter Size	Housing	Letter Colors	Number of Faces	Exit	Housing Color	Options	Accessories
Series	Letter Size	Housing	Letter Colors	Number of Faces	Exit	Housing Color	Options	Accessories
XLA2 =AC Only XLN2 =Self Powered	8 =8" ¹	D =Die Cast	R =Red	1 =One Face 2 =Two Faces	ES =Energy Efficient LEDs	_S =Silver & Black WH =White	_ =None TPS =Tamper Proof Screws	GXB =Wire Guard, Wall Mount, AC-Only Exit GXBW =Wire Guard, Wall Mount, Self Powered Exit E =End Mount
Notes: 1. NYC Code Compliant with 8" letters only.								

Product Specifications

Electronic

- Dual-voltage input 120/277 VAC, 60Hz
- Solid-state circuitry (no mechanical relay is used)
- Constant-current charger
- Sealed, maintenance-free nickel cadmium battery

- Durable die-cast aluminum housing and faceplate
- Contemporary styled, soft-corner design
- Brushed aluminum or white finish
- Easily removed, changeable directional chevrons
- Low-profile mounting canopy included

Code Compliance

- UL 924 Listed
- NFPA 101 Compliant
- NYC Code Compliant

Warranty

- 5 year product warranty
- 7 year pro-rated battery warranty